

PFEIFFER VACUUM

HICUBE 80 ECO TURBO PUMPING STATIONS

INLET FLANGE: DN 63 ISO-K, DN 40 ISO-KF, DN 63 CF-F

BACKING PUMP: MVP 015 DRY DIAPHRAGM PUMP

MAINS REQUIREMENT: 110 V, 50/60 HZ; 230 V, 50/60 HZ

POWER CONSUMPTION: 230 W

PUMPING SPEED (50HZ): $0.50 \text{ M}^3/\text{H}$

PUMPING SPEED FOR N_2 : 67 L/S

ULTIMATE PRESSURE: $< 1 \times 10^{-7} \text{ HPA}$

WEIGHT: 17 KG / 38 LBS



STATION INCLUDES:
HIPACE 80 TURBO PUMP
MVP 015 DIAPHRAGM PUMP
TPS 110
DCU 002 CONTROL UNIT

TURBO PUMPING STATIONS ARE FULLY AUTOMATIC PUMP UNITS WHICH ARE READY FOR CONNECTION. A TURBO PUMPING STATION CONSISTS OF A PORTABLE VACUUM PUMPING UNIT WITH A TURBO PUMP AND BACKING PUMP.



CONTACT US:
973.249.0854

VISIT US AT:
WWW.AJVS.COM