



PKR 361, high current, DN 40 CF-F





PKR 361, high current, DN 40 CF-F

- FullRange® gauge with two sensors in one housing
- Very low external magnetic field
- Display range from 1 · 10⁻⁹ to 1000 hPa
- Maximum pressure refers to inert gases and temperatures of less than < 55 °C
- Rugged and dependable
- Insensitive to air ingress
- Without elastomer seal
- High current version optimized for high vacuum applications

Technical Data	PKR 361, high current, DN 40 CF-F
Accuracy: 10 ⁻⁸ - 10 ² hPa	± 30 %
Anode	Molybdenum
Bakeout temperature	Elektronics removed, ≤150 °C Elektronics removed, ≤302 °F Elektronics removed, ≤423 K
Feedthrough	Glass
Filament	Tungsten
Flange	Stainless steel 1.4435
Measurement range max.	1,000 hPa 750 Torr 1,000 mbar
Measurement range min.	1 · 10 ⁻⁸ hPa 7.5 · 10 ⁻⁹ Torr 1 · 10 ⁻⁸ mbar
Method of measurement	Pirani/Cold Cathode
Nominal diameter	DN 40 CF-F
Output signal: Minimum load	10 kΩ
Output signal: Pressure range	2.0 - 8.6 V
Output signal: Sensor error above	9.5 V
Output signal: Sensor error below	10.5 V
Pressure max.	10,000 hPa 7,500 Torr 10,000 mbar
Repeatability: 10 ⁻⁸ - 10 ² hPa	± 5 %
Sensor cable length	≤ 300 m (1 mm²/wire)
Supply: Power consumption max.	2 W
Supply: Voltage	14.5-30 V DC
Temperature: Operating	5-55 °C 41-131 °F 278-328 K
Temperature: Storage	-40-70 °C -40-158 °F 233-343 K
Volume	19.9 cm ³
Weight	< 570 g

Order number	
PKR 361	PT T03 350 010

Accessories	
Accessory for ActiveLine gauges and controllers	
Mating connector	B 4707 283 MA
Sensor cable, 3 m	PT 448 250 -T

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems: We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities! We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a perfect vacuum solution? Please contact us:

Pfeiffer Vacuum GmbH Headquarters · Germany T +49 6441 802-0 info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com